

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 August 2002 (22.08.2002)

PCT

(10) International Publication Number
WO 02/065791 A1

(51) International Patent Classification⁷: **H04Q 7/00**,
H03M 11/00

(72) Inventors: **FACCIN, Stefano, M.**; 3421 Dartmoor, Dallas, TX 75229-2622 (US). **RAJANIEMI, Jarkko**; Lapinrinne 2 A 11, FIN-00180 Helsinki 18 (FI).

(21) International Application Number: PCT/IB02/00382

(22) International Filing Date: 8 February 2002 (08.02.2002)

(74) Agents: **STOUT, Donald, E.** et al.; Antonelli, Terry, Stout & Kraus, LLP, Suite 1800, 1300 North Seventeenth Street, Arlington, VA 22209 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/783,087 15 February 2001 (15.02.2001) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.


(71) Applicant: **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(71) Applicant (*for LC only*): **NOKIA INC.** [US/US]; 6000 Connection Drive, Irving, TX 75039 (US).

[Continued on next page]

(54) Title: **TECHNIQUE FOR ENABLING EMERGENCY CALL CALLBACK OF A TERMINAL WITHOUT A VALID SUBSCRIBER IDENTITY**



(57) Abstract: A technique for enabling a callback by a called party, such as an emergency center, of a terminal (410), such as a mobile terminal having no identity and no CBN (Call Back Number), in the case of an emergency call, for example, includes allocating a temporary identity to the terminal (410) and then allocating an IP address to the terminal and storing the association between the temporary identity and the allocated IP address. A CBN is that allocated to the mobile terminal and the association between the CBN and the allocated IP address is also stored. A call is then setup between the terminal and the called party (480). Upon the call between the terminal and the called party (480) being dropped, the IP address associated with the allocated CBN of the terminal is retrieved as is the stored temporary identity corresponding to the retrieved IP address. Paging is then forwarded to the terminal using the stored temporary identity and a call is again setup between the terminal (410) and the called party (480).

WO 02/065791 A1



European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

TECHNIQUE FOR ENABLING EMERGENCY CALL CALLBACK OF A TERMINAL WITHOUT A VALID SUBSCRIBER IDENTITY

TECHNICAL FIELD

The present invention relates to supporting emergency calls in, for example, an IP (Internet Protocol) based mobile network. More particularly, the present invention relates to a technique for enabling an emergency call callback of a mobile terminal, such as a mobile terminal, which does not have valid subscriber identity, such as a SIM (Subscriber Identification Module).

BACKGROUND ART

In the United States, the FCC (Federal Communications Commission) has a requirement that an emergency call center should be able to call back a caller who has made an emergency call if the call was dropped. In the case of a caller calling from a mobile terminal, upon an emergency call being dropped, the mobile network is likely to perform paging for the terminal/subscriber who made the emergency call initially. However, if the caller made the call from a mobile terminal, which did not have a valid subscriber identity, such as a SIM, the network cannot perform paging since it does not know the identity of the caller.

DISCLOSURE OF THE INVENTION

In accordance with the present invention, upon a caller making a call from a terminal to a
5 called party without a valid subscriber identity, the terminal is temporarily assigned an temporary
subscriber identity. The temporary subscriber identity includes a call back identity which the
called party can use to identify the caller terminal when calling the caller terminal back. The call
back identity can be a CBN (Call Back Number), such as an E. 164 number, which can be later
used to establish a connection to the called party.

10 Furthermore, in accordance with the present invention, the temporary subscriber identity
includes, for example, a TMSI (Temporary Mobile Subscriber Identity) or IMSI (International
Mobile Subscriber Identity), which can later be used to establish a connection to the called
terminal.

BRIEF DESCRIPTION OF THE DRAWINGS

15 The foregoing and a better understanding of the present invention will become apparent
from the following detailed description of example embodiments and the claims when read in
connection with the accompanying drawings, all forming a part of the disclosure of this
20 invention. While the foregoing and following written and illustrated disclosure focuses on
disclosing example embodiments of the invention, it should be clearly understood that the same
is by way of illustration and example only and the invention is not limited thereto. The spirit and
scope of the present invention are limited only by the terms of the appended claims.

The following represents brief descriptions of the drawings, wherein:

25 Figure 1 illustrates an example of callback number allocation for emergency calls.

Figure 2 illustrates an example of callback number allocation for mobile terminals.

Figure 3 illustrates an example of callback number allocation in accordance with the present invention.

5 Figure 4 illustrates a network node of communication system in accordance with the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

10 Before beginning a detailed description of the subject invention, mention of the following is in order. When appropriate, like reference numerals and characters may be used to designate identical, corresponding, or similar components in differing drawing figures. Furthermore, in the detailed description to follow, example sizes/models/values/ranges may be given, although the present invention is not limited thereto.

15 When a mobile terminal without a SIM card sets up an emergency call, the terminal has no identity and no E.164 number allocated to it. Accordingly, should the emergency call be dropped for any reason, the PSAP (Public Service Answering Point)/Emergency Center is unable to receive a callback E.164 number to enable the PSAP to call back the mobile terminal.

To solve the problem, in accordance with the present invention, each CSCF (Call State
20 Control Function) which is enabled to support emergency calls is provided with a set of Callback Numbers (CBN), for example, E.164 numbers, that can be allocated for callback purposes. These CBNs may be arranged such that a call setup using a CBN is always routed to the CSCF that has allocated the CBN. This routing can be achieved by arranging the network configuration and is always supported for roaming purposes.

The CSCF, upon receiving a call setup request from a non-registered mobile terminal indicating an emergency call, allocates a CBN to the terminal by associating the CBN to the IP address provided by the mobile terminal during the call setup.

5 If the call is dropped for any reason, and the emergency service needs to callback the mobile terminal, which initiated the call, the CBN is used. When the call reaches the CSCF, the CSCF retrieves the IP address of the mobile terminal and forwards the call setup to the retrieved IP address.

10 In more detail, referring to Figure 1, in step 1, an emergency call is placed by a MT (mobile terminal). In step 2, a PDP (Packet Data Protocol) context is activated utilizing the same procedure as in GPRS (General Packet Radio Service)/UMTS (Universal Mobile Terrestrial System). The activation is between the mobile terminal and the GGSN (Gateway GPRS Service Node) via the SGSN (Server GPRS Service Node). In step 3, an emergency call setup is arranged between the mobile terminal and the CSCF using the MS IP address. In step 4, the CSCF
15 determines that the mobile terminal is not registered and allocates a CBN to the calling mobile terminal. In step 5, a call setup is arranged between the CSCF and the PSAP (Public Service Answering Point)/emergency center using the CBN allocated by the CSCF. In step 6, the call between the mobile terminal and the PSAP takes place.

20 Should the call between the mobile terminal and the PSAP be dropped for any reason, as noted in step 7, and should the PSAP wish to call back the mobile terminal, a call setup is arranged in step 8 between the PSAP and the CSCF to the previously allocated CBN assigned to the calling mobile terminal. In step 9, the CSCF retrieves the MS IP address associated with the previously allocated CBN and in step 10 arranges a call setup to the mobile terminal that

originated the emergency call. In step 11, the call between the mobile terminal and the PSAP can continue.

As shown in Figure 2, in the situation where the mobile station or terminal has an IP address but does not have a CBN, that is, an E. 164 number, the mobile station or terminal establishes a VoIP call. Namely, in step 1, a call setup occurs from the MS IP address to the called party alias between the MT and the CSCF. In step 2, the CSCF detects that the MT does not have an E. 164 number and allocates a CBN to the MT. In step 3, a call setup occurs from the CBN to the called party alias, for example, the PSAP/Emergency Center. In step 4, the call between the MT and the called party takes place.

While Figures 1 and 2 each illustrates callback number allocation techniques, neither provides a complete solution to the emergency callback requirements of the FCC. Namely, the technique of Figure 1 does not provide a complete solution in that the MSC cannot page the mobile station with a CBN, that is, an E. 164 number, and therefore needs enhancement by reserving a more complete temporary subscriber identity including also an IMSI or TMSI as illustrated in Figure 2.

Figure 3 illustrates a callback number allocation technique in accordance with the present invention. In step 1, an emergency call is placed by a MT. In step 2, an activate PDP context request is forwarded from the MT to the SGSN and in step 3, the SGSN allocates a temporary ID for the calling MT, such as a TMSI or IMSI. In step 4, an activate PDP context request is forwarded from the SGSN to the GGSN and in step 5, the GGSN allocates an IP address to the calling MT. The SGSN stores the association between the temporary ID and PDP context and the IP address. In step 6, the GGSN forward's an acknowledgment of the request and returns the

allocated IP address to the SGSN which in turn returns the allocated IP address to the calling MT in step 7. In step 8, at emergency call setup occurs between the calling MT and the CSCF. In step 9, the CSCF detects that the caller is not registered and allocates a CBN to the caller and stores
5 the association between the CBN and the IP address. In step 10, a call setup occurs from the CSCF to the called party, namely, the PSAP/Emergency Center and in step 11, the call between the caller and the called party takes place.

In step 12, it is assumed that the call between the called party and the caller is dropped. Since the called party, that is, the PSAP, which is to call the caller back, in step 13, a call setup
10 occurs between the called party and the CSCF in which the CBN is forwarded to the CSCF and in step 14, the CSCF retrieves the IP address associated with the CBN. In step 15, a call setup occurs between the CSCF and the GGSN and in step 16, the GGSN detects an incoming packet for the IP address and determines the PDP context for the IP address. In step 17, the GGSN forwards the incoming packets to the SGSN via the PDP context. If in the SGSN there is no
15 radio bearer allocated for the PDP context, then the SGSN then locates the previously stored ID for the user and starts the paging with the ID. In step 18, the paging is forwarded to the calling MT. In step 19, the MT responds to the paging and the radio bearer for the PDP context is setup and the call between the MT and the PSAP takes place again.

Figure 4 illustrates a network node of a communication system in accordance with the
20 present invention. As illustrated in Figure 4, a network node 400 is connected to the remainder of the communication system. A terminal 410, such as a mobile terminal, is connected to the network node 400. A called party 480, such as an emergency communication center, is also connected to the network node 400. The network node 400

includes a receiver 430 for receiving a request for a connection from the terminal 410 to the called party 480. A detector 440, included in the network node 400, detects that the terminal 410 has no identity enabling callback. An allocator 450, in response to a signal from the
5 detector 440, allocates a temporary identity to the terminal 410, the temporary identity being a callback identity which can be used by the called party 480 to identify the terminal 410 for terminating connections. A controller 460, included in the network node 400, sets up a connection between the terminal 410 and the called party 480. An indicator 470, also included in the network node 400, indicates the callback identity to the called party 480.

10 This concludes the description of the example embodiments. Although the present invention has been described with reference to illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled of the art that will fall within the spirit and scope of the principles of this invention. More particularly, reasonable variations and modifications are possible in the component parts and/or
15 arrangements of the subject combination arrangement within the scope of the foregoing disclosure, the drawings, and the appended claims without departing from the spirit of the invention. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

CLAIMS

What is claimed is:

1. A method of enabling a callback by a called party of a terminal having no call
5 back identity, the method comprising:

 requesting connection from the terminal to a called party,

 detecting that the terminal has no identity enabling callback;

 allocating a temporary identity to the terminal, the temporary identity comprising a
call back identity which can be used by the called party to identify the terminal for terminating
10 connections;

 setting up a connection between the terminal and the called party and indicating
the call back identity to the called party.
2. The method of claim 1, wherein, upon the connection between the terminal and
15 the called party being dropped, the method further comprising:

 the called party requesting a connection using the call back identity of the
terminal;

 receiving the connection request including the call back identity;

 retrieving the temporary identity of the terminal; and establishing a connection to
20 the terminal.
3. The method of claim 1, wherein the temporary identity comprises an IP address for the
terminal.

4. The method of claim 1, wherein the call back identity comprises an E.164 number.

5 5. The method of claim 1, wherein the call back identity comprises an IP address.

6. The method of claim 1, wherein the temporary identity comprises an IMSI
(International Mobile Subscriber Identity).

10 7. The method of claim 2, wherein the temporary identity comprises an IMSI
(International Mobile Subscriber Identity).

8. The method of claim 1, wherein the temporary identity comprises a TMSI
(Temporary Mobile Subscriber Identity).

15 9. The method of claim 2, wherein the temporary identity comprises a TMSI
(Temporary Mobile Subscriber Identity).

20 10. The method of claim 1, wherein the terminal has an IP address enabling
terminating connections to the terminal but no CBN (Call Back Number), the method further
comprising:

detecting that the terminal has no CBN;

allocating a CBN to the terminal upon detecting that the mobile terminal has no CBN and storing association between the CBN and the IP address of the terminal;

setting up a call between the terminal and the called party, and

5 indicating the call back number to the called party..

11. The method of claim 10, wherein the CBN comprises an E. 164 number.

10 12. The method of claim 1, wherein:

the terminal requests the connection to the called party by forwarding a PDP context request to an SGSN (Server General Packet Radio Service Node);

the SGSN allocates a temporary identity to the terminal;

15 the SGSN forwards the activate PDP context request to a GGSN (Gateway General Packet Radio Service Node);

the GGSN allocates an IP address to the terminal and stores association between the temporary identity and the allocated IP address;

the GGSN forwards the allocated IP address to the terminal via the SGSN;

20 a call setup is communicated between the terminal and a CSCF (Call State Control Function) using the allocated IP address;

the CSCF detects that the terminal is not registered and allocates a CBN (Call Back Number) and stores association between CBN and allocated IP address; and

the CSCF sets up a call between the terminal and the called party.

13. The method of claim 12, wherein, upon the call between the terminal and the called party being dropped, the method further comprising:

5 communicating a call setup from the called party to the CSCF;
 the CSCF retrieving the IP address associated with the CBN and then forwarding the call setup to the GGSN;

 the GGSN retrieving the stored identity for the IP address and forwarding paging to the terminal via the SGSN; and

10 again setting up a call between the terminal and the called party by providing a new PDP context activation.

14. The method of claim 12, wherein the temporary identity comprises an IMSI (International Mobile Subscriber Identity).

15 15. The method of claim 13, wherein the temporary identity comprises an IMSI (International Mobile Subscriber Identity).

16. The method of claim 12, wherein the temporary identity comprises a TMSI (Temporary Mobile Subscriber Identity).

20 17. The method of claim 13, wherein the temporary identity comprises a TMSI (Temporary Mobile Subscriber Identity).

18. The method of claim 12, wherein the CBN comprises an E. 164 number.

5 19. The method of claim 13, wherein the CBN comprises an E. 164 number.

20. A communication system for enabling a callback by a called party of a terminal having no call back identity, the system comprising:

10 a receiving means for receiving a request for a connection from the terminal to a called party;

a detecting means for detecting that the terminal has no identity enabling callback;

an allocation means for allocating a temporary identity to the terminal, the temporary identity comprising a call back identity which can be used by the called party to identify the terminal for terminating connections;

15 a connection control means for setting up a connection between the terminal and the called party; and

an indication means for indicating the call back identity to the called party.

21. A network node of a communication system for enabling a callback by a called party of a terminal having no call back identity, the network node comprising:

20 a receiving means for receiving a request for a connection from the terminal to a called party;

a detecting means for detecting that the terminal has no identity enabling callback

an allocation means for allocating a temporary identity to the terminal, the temporary identity comprising a call back identity which can be used by the called party to identify the terminal for terminating connections;

5 a connection control means for setting up a connection between the terminal and the called party; and

an indication means for indicating the call back identity to the called party.

FIG. 1




FIG. 2




FIG. 3





FIG. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB02/00382

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : Please See Extra Sheet.

US CL : Please See Extra Sheet.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 455/404, 458, 459, 432, 433

379/37, 45, 46

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EAST SEARCH AND WEST SEARCH

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X — Y, P	US 5,937,344 A (ZICKER) 10 AUGUST 1999, COL. 1, LINE 30 TO COL. 11, LINE 34	1, 2, 20, 21 — 3-9, 10, 11
Y, P	US 6,240,462 B1 (AGRAHARAM ET AL.) 29 MAY 2001, COL. 3, LINE 28 TO COL. 4, LINE 65.	3-5, 10, 11
Y, P	US 6,223,046 B1 (HAMILL-KEAYS ET AL.) 24 APRIL 2001, COL. 4, LINE 20 TO COL. 5, LINE 48.	6-9

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

"A"	document defining the general state of the art which is not considered to be of particular relevance	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E"	earlier document published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	"&"	document member of the same patent family
"P"	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

02 JUNE 2002

Date of mailing of the international search report

08 JUL 2002

Name and mailing address of the ISA/US .

Commissioner of Patents and Trademarks

Box PCT

Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

JEAN A. CELIN

Telephone No. (703) 305-4847

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB02/00382

A. CLASSIFICATION OF SUBJECT MATTER:

IPC (7):

H04Q 7/00

H03M 11/00

A. CLASSIFICATION OF SUBJECT MATTER:

US CL :

455/404, 458, 459, 432, 433

379/37, 45, 46